





  
ducati.com

Riding a motorcycle is the most exciting way to enjoy the road, and offering the utmost safety to the motorcyclist is Ducati's commitment. Ducati bikes are increasingly easy to handle, reliable and better equipped to guarantee maximum safety and enhance riding pleasure. Technical clothing is made with more and more advanced materials for adequate protection and increased visibility. The safety of motorcyclists is Ducati's commitment. For more information visit the safety section of the Ducati site ([www.ducati.com](http://www.ducati.com)).

**Warning:** The photos and technical information in this catalogue may refer to prototypes subject to modifications during production and are purely for illustration and reference purposes, and are therefore not binding on Ducati Motor Holding S.p.A. Sole Shareholder Company - Company subject to the direction and coordination of AUDI AG ("Ducati"). Ducati cannot be held responsible for any print and/or translation errors. This catalogue is transnational and therefore some products may not be available and/or their features may vary in accordance with local laws. Not all colours and versions are available in each country. Ducati reserves the right to make changes and improvements to any product without obligation of prior notice or to make such changes to products already sold. Further characteristics of the products are contained in the pertinent owner's manuals. The products represented are not definitive versions and are therefore subject to significant changes at Ducati's discretion without prior notice. The photographs published in this catalogue show only professional riders under controlled street conditions. Do not attempt to imitate such riding behaviour as it could be dangerous for you or other people on the road. This catalogue, including but not limited to the trademarks, logos, texts, images, graphics and table of contents herein, constitute Ducati intellectual property, or in any event Ducati has the right to reproduce it; any reproduction, modification or other whole or partial use of the catalogue or its contents, including publication on the Internet without the prior written consent of Ducati, is prohibited.

Actual fuel consumption may vary based on many factors, including but not limited to riding style, maintenance performed, weather conditions, surface characteristics, tyre pressure, load, weight of the rider and the passenger, accessories.

Ducati indicates the dry weight of the motorcycle excluding battery, lubricants and coolants for liquid-cooled models. The weights in running order are considered with all operating fluids, standard equipment and the fuel tank filled to 90% of its useful capacity (UE regulation no. 168/2013). For more information visit [www.ducati.com](http://www.ducati.com). November 2023

Developed with  Technical partner 



# HYPERMOTARD 698 MONO





# Live. Play. Ride.

Climb aboard and let fun take charge. The new Hypermotard 698 Mono is the first single-cylinder road-going Supermotard by Ducati, born with just one aim – to transmit excitement, dominating the scene.

Simple, lightweight, and agile, it is a true “fun-bike” with racing DNA.

## Hypermotard 698 Mono Technical data

Engine	
<b>Engine</b>	Superquadro Mono, single-cylinder, 4 valves per cylinder, Desmodromic timing, 2-balance countershafts, liquid cooled
<b>Displacement</b>	659 cc
<b>Bore X Stroke</b>	116 x 62.4 mm
<b>Power</b>	57 kW (77.5 hp) @ 9,750 rpm
<b>Torque</b>	63 Nm (46.5 lb-ft) @ 8,000 rpm
<b>Fuel injection</b>	Electronic fuel injection system, Øe 62 mm throttle body with full Ride by Wire system
<b>Exhaust</b>	1-2 exhaust system, double aluminum mufflers, catalytic converter and lambda probe
Transmission	
<b>Gearbox</b>	6 speed
<b>Final drive</b>	Chain 520; Front sprocket 15; Rear sprocket 42
<b>Clutch</b>	Slipper and self-servo wet multiplate clutch, hydraulic control
Chassis	
<b>Frame</b>	Tubular steel Trellis frame
<b>Front suspension</b>	Ø 45 mm Marzocchi fully adjustable aluminum fork

<b>Rear Suspension</b>	Progressive linkage with Sachs fully adjustable monoshock. Aluminium double-sided swingarm
<b>Tyre (front/rear)</b>	Pirelli Diablo Rosso IV, 120/70 ZR17 Pirelli Diablo Rosso IV, 160/60 ZR17
<b>Wheel (front/rear)</b>	Y shaped 5-spoke light alloy 3.5" x 17" Y shaped 5-spoke light alloy 5.0" x 17"

<b>Wheel travel (front/rear)</b>	215 mm (8.5 in) - 240 mm (9.4 in)
----------------------------------	-----------------------------------

<b>Front brake</b>	Ø 330 mm aluminum flange disc, Brembo M4.32 calliper, radial pump with adjustable lever, with Bosch Cornering ABS
--------------------	-------------------------------------------------------------------------------------------------------------------

<b>Rear brake</b>	Ø 245 mm disc, single piston floating calliper, with Bosch Cornering ABS
-------------------	--------------------------------------------------------------------------

<b>Instrumentation</b>	3.8" LCD display with Improved Black Nematic (IBN) technology
------------------------	---------------------------------------------------------------

Dimensions and Weights	
<b>Wet weight no fuel</b>	151 kg (333 lb)
<b>Seat height</b>	904 mm (35.6 in) 889 mm (35.0 in) with low seat accessory
<b>Wheelbase</b>	1,443 mm (56.8 in)
<b>Fuel tank capacity</b>	12 l (3 US gallons)

Safety equipment	
	Riding Modes, Bosch Cornering ABS, Ducati Traction Control (DTC), Ducati Wheelie Control (DWC), Engine Brake Control (EBC), Ducati Brake Light (DBL)*

<b>Front suspension</b>	Ø 45 mm Marzocchi fully adjustable aluminum fork
-------------------------	--------------------------------------------------

<b>Standard equipment</b>	Power Modes, Ducati Power Launch (DLC), Full LED lighting system, Daytime Running Lights (DRL)*, Tapered aluminum handlebars, Lithium-ion battery
---------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------

<b>Provided equipment</b>	Passenger footpegs
---------------------------	--------------------

Ready For	
	Anti-theft system, Ducati Quick Shift (DQS) Up/Down, Heated grips, Ducati Multimedia System (DMS).

Warranty and Maintenance	
<b>Warranty</b>	24 months unlimited mileage
<b>Maintenance</b>	15,000 km (9,000 miles)/24 months
<b>Valve clearance check</b>	30,000 km (18,000 mi)

Emissions and Consumption**	
<b>Standard</b>	Euro 5
<b>CO<sub>2</sub> emissions</b>	112 g/km
<b>Consumption</b>	4.8 l/100 km

\*Bike specifications and equipment may vary from market to market. Please refer to your local dealer for further information  
\*\* Only for countries where Euro 5 standard applies.



## Hypermotard 698 Mono Technical data

Engine	
<b>Engine</b>	Superquadro Mono, single-cylinder, 4 valves per cylinder, Desmodromic timing, 2-balance countershafts, liquid cooled
<b>Displacement</b>	659 cc
<b>Bore X Stroke</b>	116 x 62.4 mm
<b>Power</b>	57 kW (77.5 hp) @ 9,750 rpm
<b>Torque</b>	63 Nm (46.5 lb-ft) @ 8,000 rpm
<b>Fuel injection</b>	Electronic fuel injection system, Øe 62 mm throttle body with full Ride by Wire system
<b>Exhaust</b>	1-2 exhaust system, double aluminum mufflers, catalytic converter and lambda probe
Transmission	
<b>Gearbox</b>	6 speed with Ducati Quick Shift Up/Down
<b>Final drive</b>	Chain 520; Front sprocket 15; Rear sprocket 42
<b>Clutch</b>	Slipper and self-servo wet multiplate clutch, hydraulic control
Chassis	
<b>Frame</b>	Tubular steel Trellis frame
<b>Front suspension</b>	Ø 45 mm Marzocchi fully adjustable aluminum fork

<b>Rear Suspension</b>	Progressive linkage with Sachs fully adjustable monoshock. Aluminium double-sided swingarm
<b>Tyre (front/rear)</b>	Pirelli Diablo Rosso IV, 120/70 ZR17 Pirelli Diablo Rosso IV, 160/60 ZR17
<b>Wheel (front/rear)</b>	Y shaped 5-spoke light alloy 3.5" x 17" Y shaped 5-spoke light alloy 5.0" x 17"

<b>Wheel travel (front/rear)</b>	215 mm (8.5 in) - 240 mm (9.4 in)
----------------------------------	-----------------------------------

<b>Front brake</b>	Ø 330 mm aluminum flange disc, Brembo M4.32 calliper, radial pump with adjustable lever, with Bosch Cornering ABS
--------------------	-------------------------------------------------------------------------------------------------------------------

<b>Rear brake</b>	Ø 245 mm disc, single piston floating calliper, with Bosch Cornering ABS
-------------------	--------------------------------------------------------------------------

<b>Instrumentation</b>	3.8" LCD display with Improved Black Nematic (IBN) technology
------------------------	---------------------------------------------------------------

Dimensions and Weights	
<b>Wet weight no fuel</b>	151 kg (333 lb)
<b>Seat height</b>	904 mm (35.6 in) 889 mm (35.0 in) with low seat accessory
<b>Wheelbase</b>	1,443 mm (56.8 in)
<b>Fuel tank capacity</b>	12 l (3 US gallons)

Safety equipment	
	Riding Modes, Bosch Cornering ABS, Ducati Traction Control (DTC), Ducati Wheelie Control (DWC), Engine Brake Control (EBC), Ducati Brake Light (DBL)*

<b>Standard equipment</b>	Power Modes, Ducati Power Launch (DLC), Ducati Quick Shift (DQS) Up/Down, Full LED lighting system, Daytime Running Lights (DRL)*, Tapered aluminum handlebars, Lithium-ion battery
---------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


<b>Provided equipment</b>	Passenger footpegs
---------------------------	--------------------

Ready For	
	Anti-theft system, Heated grips, Ducati Multimedia System (DMS)

Warranty and Maintenance	
<b>Warranty</b>	24 months unlimited mileage
<b>Maintenance</b>	15,000 km (9,000 miles)/24 months
<b>Valve clearance check</b>	30,000 km (18,000 mi)

Emissions and Consumption**	
<b>Standard</b>	Euro 5
<b>CO<sub>2</sub> emissions</b>	112 g/km
<b>Consumption</b>	4.8 l/100 km

\*Bike specifications and equipment may vary from market to market. Please refer to your local dealer for further information  
\*\* Only for countries where Euro 5 standard applies.



\*Equal to 18,000 miles.



\*Equal to 18,000 miles.